

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product Description: Xylene
Cat No. : X/0200/17, X/0200/27, X/0200/21, X/0200/08, X/0200/25, X/0200/DH25, X/0200/PB17, X/0200/21RSS, X/0200/24RSS, X/0200/25RSS, X/0200/34RSS, X/0200/27RSS
CAS No 1330-20-7
Molecular Formula C8 H10

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Details of the supplier of the safety data sheet

Importer Fisher Scientific Korea D5,D6, Incheon Airport Logistics Complex 150, Gonghangdong-Ro 296 Beon-Gil Jung-Gu, Incheon Tel: +82-1661-9555 Fax: +82-2-2023-0603	Supplier Fisher Scientific UK Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom
---	---

E-mail address Chem.KR@thermofisher.com

Emergency Telephone Number

Emergency telephone: Medical: +(82) 070-7686-0086 or + 1-703-741-5970
CHEMTREC: 080 822 1374 (Local), CHEMTREC: 1-800-424-9300 or + 1-703-527-3887
Korea: 00-308-13-2549 (24 hours a day, 7 days a week)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Physical hazards

Flammable liquids Category 3

Health hazards

Acute Dermal Toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Specific target organ toxicity - (repeated exposure)	Category 1

Environmental hazards

Based on available data, the classification criteria are not met

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

Label Elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs through prolonged or repeated exposure
H312 + H332 - Harmful in contact with skin or if inhaled

Precautionary Statements

Prevention

P243 - Take action to prevent static discharges
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground and bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P242 - Use non-sparking tools
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
P321 - Specific treatment (see supplemental first aid instructions on this label)
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P312 - Call a POISON CENTER or doctor if you feel unwell
P362 + P364 - Take off contaminated clothing and wash it before reuse
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention
P314 - Get medical advice/attention if you feel unwell

Storage

P403 + P235 - Store in a well-ventilated place. Keep cool
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Toxic to terrestrial vertebrates

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

This product does not contain any known or suspected endocrine disruptors

NFPA

Health
3

Flammability
2

Instability
0

Physical hazards
N/A

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	Common Name	CAS No	Index No	Weight %
Xylenes (o-, m-, p- isomers)	Dimethylbenzene	1330-20-7	KE-35427	99 - 100

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray. Alcohol resistant foam. Dry chemical. Carbon dioxide (CO₂). Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

Hazardous Combustion Products

None under normal use conditions.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	CAS No	Korea	ACGIH TLV	OSHA PEL
Xylenes (o-, m-, p- isomers)	1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 435 mg/m ³ (Vacated) STEL: 150 ppm (Vacated) STEL: 655 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³

Component	CAS No	European Union	The United Kingdom	Germany
Xylenes (o-, m-, p- isomers)	1330-20-7	TWA: 50 ppm (8h) TWA: 221 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 442 mg/m ³ (15min)	STEL: 100 ppm 15 min STEL: 441 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 220 mg/m ³ 8 hr	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 220 mg/m ³ (8 Stunden). AGW - exposure

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

		Skin	Skin	factor 2 TWA: 50 ppm (8 Stunden). MAK all isomers TWA: 220 mg/m ³ (8 Stunden). MAK all isomers Höhepunkt: 100 ppm Höhepunkt: 440 mg/m ³ Haut Haut all isomers
--	--	------	------	---

ACGIH - Biological Exposure Indices

Component	CAS No	ACGIH - Biological Exposure Indices
Xylenes (o-, m-, p- isomers)	1330-20-7	1.5 g/g creatinine Medium: urine Time: end of shift Determinant: Methylhippuric acids

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Personal protective equipment

Respiratory Protection

Use only those certified by the Korea Occupational Safety and Health Administration.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system Local authorities should be advised if significant spillages cannot be contained

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

Appearance (Physical State, Color, etc.)	Colourless Liquid	
Odor	aromatic	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	-34 °C / -29.2 °F	
Softening Point	No data available	
Boiling Point/Range	136 - 140 °C / 276.8 - 284 °F	@ 760 mmHg
Flash Point	23 °C / 73.4 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1% (V) Upper 7% (V)	
Vapor Pressure	8 mbar @ 20°C	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	0.865	
Bulk Density	Not applicable	Liquid
Water Solubility	Insoluble	
Solubility in other solvents	No information available	

Partition Coefficient (n-octanol/water)

Component	CAS No	log Pow
Xylenes (o-, m-, p- isomers)	1330-20-7	3.15

Autoignition Temperature	463 °C	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties		explosive air/vapour mixtures possible
Oxidizing Properties	No information available	
Molecular Formula	C8 H10	
Molecular Weight	106.17	

SECTION 10: STABILITY AND REACTIVITY

Reactivity
None known, based on information available

Chemical Stability
Stable under normal conditions.

Possibility of Hazardous Reactions
Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

Conditions to Avoid
Keep away from open flames, hot surfaces and sources of ignition.

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

Incompatible Materials

None known.

Hazardous Decomposition Products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

Information on expected route of exposure

Inhalation Avoid breathing vapors or mists. Harmful by inhalation.
Ingestion Harmful if swallowed. Potential for aspiration if swallowed.
Eyes Avoid contact with eyes. Irritating to eyes. Vapor may cause irritation.
Skin Avoid contact with skin. May cause irritation. Prolonged skin contact may defat the skin and produce dermatitis. Harmful in contact with skin.

Information on Health Hazards

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Category 4
Inhalation Category 4

Component	CAS No	LD50 Oral	LD50 Dermal	LC50 Inhalation
Xylenes (o-, m-, p- isomers)	1330-20-7	LD50 = 3500 mg/kg (Rat)	LD50 > 4350 mg/kg (Rabbit)	29.08 mg/L [MOE Risk Assessment Vol.1, 2002]

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

Component	CAS No	Test method	Test species	Study result
Xylenes (o-, m-, p- isomers)	1330-20-7	No data available	No data available	No data available

(e) germ cell mutagenicity; No data available

Component	CAS No	Test method	Test species	Study result
Xylenes (o-, m-, p- isomers)	1330-20-7	No data available	No data available	No data available

(f) carcinogenicity; No data available

Component	CAS No	Test method	Test species / Duration	Study result
Xylenes (o-, m-, p- isomers)	1330-20-7	No data available	No data available	No data available

There are no known carcinogenic chemicals in this product

Component	CAS No	IARC	NTP	ACGIH	OSHA	UK
Xylenes (o-, m-, p- isomers)	1330-20-7	Not listed	Not listed	Not listed	Not listed	Not listed

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

(g) reproductive toxicity; No data available

Component	CAS No	Test method	Test species / Duration	Study result
Xylenes (o-, m-, p- isomers)	1330-20-7	No data available	No data available	No data available

(h) STOT-single exposure; Category 3
Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Category 1
Target Organs No information available.

(j) aspiration hazard; No data available

Other Adverse Effects

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Component	CAS No	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable	Not applicable

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms.

Component	CAS No	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Xylenes (o-, m-, p- isomers)	1330-20-7	LC50: 30.26 - 40.75 mg/L, 96h static (Poecilia reticulata) LC50: = 780 mg/L, 96h semi-static (Cyprinus carpio) LC50: 23.53 - 29.97 mg/L, 96h static (Pimephales promelas) LC50: > 780 mg/L, 96h (Cyprinus carpio) LC50: 7.711 - 9.591 mg/L, 96h static (Lepomis macrochirus) LC50: = 19 mg/L, 96h (Lepomis macrochirus) LC50: 13.1 - 16.5 mg/L, 96h flow-through (Lepomis macrochirus) LC50: 13.5 - 17.3 mg/L, 96h (Oncorhynchus mykiss) LC50: 2.661 - 4.093 mg/L, 96h static	LC50: = 0.6 mg/L, 48h (Gammarus lacustris) EC50: = 3.82 mg/L, 48h (water flea)	No data available	EC50 = 0.0084 mg/L 24 h

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

		(Oncorhynchus mykiss) LC50: = 13.4 mg/L, 96h flow-through (Pimephales promelas)			
--	--	--	--	--	--

Persistence and degradability

Persistence

Persistence is unlikely.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Xylenes (o-, m-, p- isomers)	3.15	0.6 - 15 dimensionless

Mobility in soil

Spillage unlikely to penetrate soil. The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility.

Ozone Depletion Potential

Component	CAS No	Ozone Depletion Potential
Xylenes (o-, m-, p- isomers)	1330-20-7	Not listed

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose in accordance with the Wastes Control Act (폐기물관리법).

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

SECTION 14: TRANSPORT INFORMATION

Road and Rail Transport

UN-No UN1307
Proper Shipping Name XYLENES
Hazard Class 3
Packing Group III

IATA

UN-No UN1307
Proper Shipping Name XYLENES
Hazard Class 3
Packing Group III

IMDG/IMO

UN-No UN1307
Proper Shipping Name XYLENES
Hazard Class 3

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

Packing Group
Marine Pollutant

III
No hazards identified

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Legend: X - Listed '-' - Not Listed

International Inventories

Component	CAS No	KECL	TSCA	EINECS	IECSC	DSL	NDSL	PICCS	ENCS	ISHL	AICS
Xylenes (o-, m-, p- isomers)	1330-20-7	KE-35427	X	215-535-7	X	X	-	X	X	X	X

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable	Not applicable	Annex I - Y42

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	Not applicable	Not applicable

Korean National Regulations

Component	CAS No	Act on Registration and Evaluation of Chemical Substances (K-REACH)	Authorised Chemicals	Existing Substances Subject to Registration
Xylenes (o-, m-, p- isomers)	1330-20-7	Annex 1 - KE-35427	Not applicable	Listed

Component	CAS No	Chemical Control Act - Toxic Chemicals	Chemical Control Act - Prohibited Chemicals	Chemical Control Act - Use Restricted Chemicals
Xylenes (o-, m-, p- isomers)	1330-20-7	1997-1-0275 (>85%)	Not applicable	Not applicable

Component	CAS No	Chemical Control Act - Accident Precaution Chemicals (% in mixtures)	Chemical Control Act - Accident Precaution Chemicals - Quantity limits Storage (% in mixtures)	Chemical Control Act - Accident Precaution Chemicals - Quantity limits Manufacture/Use (% in mixtures)
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable	Not applicable

Component	CAS No	Waste Control Law	Ministry of Environment - CMR risk	Ministry of Environment - Critically Controlled Substance
Xylenes (o-, m-, p- isomers)	1330-20-7	> 85% (CCA)	Not applicable	STOT

CCA = Chemical Control Act

Component	CAS No	ISHA - Harmful Agents Subject to Work Environment Monitoring	ISHA - Prohibited substances	ISHA - Substances requiring permission
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	Not applicable	Not applicable

Component	CAS No	ISHA - Substances	ISHA - Harmful Agents	ISHA - Permissible

SAFETY DATA SHEET

Xylenes

Revision Date 07-Jun-2024

		subject to control	Requiring Health Examination	Exposure Limits
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	Listed	Not applicable

Component	CAS No	ISHA - Subject to Process Safety Reports (minimum quantity)	ISHA - Threshold Limit Values (TLVs) Chemicals	ISHA - Special management materials
Xylenes (o-, m-, p- isomers)	1330-20-7	5000 kg	STEL: 150 ppm TWA: 100 ppm	Not applicable

National Fire Association - Dangerous Substances Minimum quantity requiring a permit

Component	CAS No	Class 1 - Oxidising solids	Class 2 - Flammable solid	Class 3 - Spontaneously Combustible Substances and Dangerous Substances When Wet	Class 4 - Flammable liquids	Class 5 - Self-reactive substances	Class 6 - Oxidising liquids
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable	Not applicable	4. Group 2 Petroleum (Insoluble) 1000 L	Not applicable	Not applicable

Control Parameters

Component	CAS No	Korea	ACGIH - Biological Exposure Indices
Xylenes (o-, m-, p- isomers)	1330-20-7	STEL: 150 ppm TWA: 100 ppm	1.5 g/g creatinine Medium: urine Time: end of shift Determinant: Methylhippuric acids

US Management Information

OSHA - Occupational Safety and Health Administration

Not applicable

Component	CAS No	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355)

Component	CAS No	CERCLA Extremely Hazardous Substances RQs	Hazardous Substances RQs	SARA 313 - Threshold Values %
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	100 lb	1.0 %

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Danger.

H226 - Flammable liquid and vapor. H304 - May be fatal if swallowed and enters airways. H312 + H332 - Harmful in contact with skin or if inhaled. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H373 - May cause damage to organs through prolonged or repeated exposure. H412 - Harmful to aquatic life with long lasting effects.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 - Immediately call a POISON CENTER or doctor/physician.

SAFETY DATA SHEET

Xylene

Revision Date 07-Jun-2024

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 31-May-2018

Revision Date 07-Jun-2024

Revision Number 8

Revision Summary SDS sections updated.

MOEL's Public Notice No. 2023-9 (Standards for Classification and Labeling of Chemical Substances and Safety Data Sheets)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet