

SCIENTIFIC

Page 1/9 Creation Date 20-Apr-2010 Revision Date 07-Mar-2024 Version 3

ALFAA30765

(+/-)-Propylene oxide

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明:	(+/-)-环氧丙烷,99+%
Product Description:	(+/-)-Propylene oxide
Cat No. :	30765
Synonyms	1,2-Epoxypropane; Methyloxirane
CAS No	75-56-9
Molecular Formula	C3 H6 O
Supplier	Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific) Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608
Emergency Telephone Number	For information US call: 001-800-227-6701 / Europe call: +32 14 57 52 11 Emergency Number US: 001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No. US: 001-800-424-9300 / Europe: 001-703-527-3887
E-mail address	begel.sdsdesk@thermofisher.com
Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

SECTION 2. HAZARD IDENTIFICATION

Physical State	Appearance	Odor
Liquid	Colorless	aromatic
Extremely flammable liquid and vapor. Cause respiratory irritation. Harmful if swallow	Emergency Overview es skin irritation. Causes serious eye irritat wed. Toxic in contact with skin. Toxic if inh polymerization may occur.	

Classification of the substance or mixture

Flammable liquids.	Category 1
Acute Oral Toxicity	Category 4
Acute Dermal Toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity - (single exposure)	Category 3

Label Elements

(+/-)-Propylene oxide



Signal Word

Danger

Hazard Statements

- H224 Extremely flammable liquid and vapor
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H340 May cause genetic defects
- H335 May cause respiratory irritation
- H302 Harmful if swallowed
- H350 May cause cancer

H311 + H331 - Toxic in contact with skin or if inhaled

Precautionary Statements

Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P240 Ground and bond container and receiving equipment
- P241 Use explosion-proof electrical/ ventilating/ lighting equipment
- P242 Use non-sparking tools
- P271 Use only outdoors or in a well-ventilated area
- P243 Take action to prevent static discharges
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P280 Wear eye protection/ face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P311 - Call a POISON CENTER or doctor

- P330 Rinse mouth
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P405 - Store locked up

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

Vapors may cause flash fire or explosion. Extremely flammable. Hazardous polymerization may occur.

Health Hazards

Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause respiratory irritation. Harmful if swallowed. Toxic in contact with skin. Toxic if inhaled. May cause cancer.

Environmental hazards

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Will likely be mobile in the environment due to its volatility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Other Hazards

Hazardous polymerization may occur. Toxic to terrestrial vertebrates. This product does not contain any known or suspected endocrine disruptors.

(+/-)-Propylene oxide

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Propylene oxide	75-56-9	>95

SECTION 4. FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.

Ingestion

Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and effects

. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Specific Hazards Arising from the Chemical

Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

(+/-)-Propylene oxide

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

Specific Use(s)

Use in laboratories

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	China	Taiwan	Thailand	Hong Kong
Propylene oxide	TWA: 5 mg/m ³	TWA: 20 ppm	TWA: 100 ppm	-
	_	TWA: 48 mg/m ³		

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Propylene oxide	TWA: 2 ppm	(Vacated) TWA: 20	IDLH: 400 ppm	STEL: 3 ppm 15 min	TWA: 2.4 mg/m ³ (8h)
		ppm		STEL: 7.2 mg/m ³ 15	TWA: 1 ppm (8h)
		(Vacated) TWA: 50		min	
		mg/m³		TWA: 1 ppm 8 hr	
		TWA: 100 ppm		TWA: 2.4 mg/m ³ 8 hr	
		TWA: 240 mg/m ³		Carc.	

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH: NIOSH - National Institute for Occupational Safety and Health

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Exposure Controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

(+/-)-Propylene oxide

Personal protective equipment

Eye Protection	Eye ProtectionGoggles (European standard - EN 166)				
Hand Protection	Protectiv	ve gloves			
Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments	
Neoprene gloves	< 30 minutes	0.6 mm	EN 374	(minimum requirement)	
PVA	< 35 minutes	0.3 mm			
Laminated film (Barrier)	> 480 minutes	0.06 mm			
Inspect gloves before use					

In

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection	Long sleeved clothing
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.
Environmental exposure controls	No information available.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Colorless	
Physical State	Liquid	
Odor	aromatic	
Odor Threshold	No data available	
рН	No information available	
Melting Point/Range	-112 °C / -169.6 °F	
Softening Point	No data available	
Boiling Point/Range	34 °C / 93.2 °F	
Flash Point	-37 °C / -34.6 °F	Method - No information available
Evaporation Rate	No information available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.9 Vol%	
	Upper 45 Vol%	
Vapor Pressure	590 mbar @ 20 °C	
Vapor Density	2.0	(Air = 1.0)
Specific Gravity / Density	0.830	
Bulk Density	Not applicable	Liquid

(+/-)-Propylene oxide

Water Solubility	40g/100ml (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/w	vater)	
Component	log Pow	
Propylene oxide	1	
Autoignition Temperature	430 °C / 806 °F	
Decomposition Temperature	No data available	
Viscosity	0.32 mPa s at 20 °C	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	
Molecular Formula	C3 H6 O	
Molecular Weight	58.08	

SECTION 10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Hazardous Reactions Hazardous Polymerization	None under normal processing. Hazardous polymerization may occur.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
Materials to avoid	Strong oxidizing agents. Acids. Bases. Amines. copper. Copper alloys. Peroxides.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11. TOXICOLOGICAL INFORMATION

Product Information

(a)	acute	toxicity;
-----	-------	-----------

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Propylene oxide	LD50 = 520 mg/kg (Rat)	LD50 = 1244 mg/kg(Rabbit)	9.48 mg/L (Rat)4 h
b) skin corrosion/irritation;	No data available		
c) serious eye damage/irritation;	Category 2		
(d) respiratory or skin sensitization; Respiratory Skin	No data available No data available		
(e) germ cell mutagenicity;	Category 1B May cause heritable genetic d	amage	
(f) carcinogenicity;	Category 1B May cause cancer. The table b ingredient as a carcinogen	pelow indicates whether each a	gency has listed any

Component	EU	UK	Germany	IARC
Propylene oxide	Carc Cat. 1B			Group 2B

SAFETY DATA SHEET

(+/-)-Propylene oxide

	o data available					
(h) STOT-single exposure; Ca		No data available				
	ategory 3					
Results / Target organs	espiratory system					
(i) STOT-repeated exposure; No	lo data available					
Target Organs No	lo information availabl	le.				
(j) aspiration hazard; No	lo data available					
	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting					
S	SECTION 12. ECO	LOGICAL INFORMA	ATION			
Ecotoxicity effects Do not empty into drains						
Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox		
Propylene oxide L	C50: = 215 mg/L, 96h static (Lepomis macrochirus)	EC50: = 350 mg/L, 48h (Daphnia magna)		EC50 = 3300 mg/L 160 min		
Persistence Pe	Not readily biodegradable Persistence is unlikely, based on information available. Bioaccumulation is unlikely					
		Pow	Bioconcentration factor (BCF)			
Component	Ιοα		No data available			

Mobility in soil	The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Will likely be mobile in the environment due to its volatility Disperses rapidly in air			
Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential	This product does not contain any known or suspected endocrine disruptors This product does not contain any known or suspected substance This product does not contain any known or suspected substance			
	SECTION 13. DISPOSAL CONSIDERATIONS			
Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.			
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.			
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.			

SECTION 14. TRANSPORT INFORMATION

(+/-)-Propylene oxide

|--|

UN-No	UN1280
Proper Shipping Name	PROPYLENE OXIDE
Hazard Class	3
Packing Group	I
IMDG/IMO	
UN-No	UN1280
Proper Shipping Name	PROPYLENE OXIDE
Hazard Class	3
Packing Group	I
IATA	
UN-No	UN1280
Proper Shipping Name	PROPYLENE OXIDE
Hazard Class	3
Packing Group	I
Special Precautions for User	No special precautions required

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The	List of	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
		dangerous goods GB 12268 - 2012										
Propylene oxide	Х	Х	Х	Х	200-879-2	Х	Х	Х	Х	Х	Х	KE-24565

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Propylene oxide	5 tonne	50 tonne

National Regulations

SECTION 16. OTHER INFORMATION

Prepared By			
Creation Date			
Revision Date			
Revision Summary			

Health, Safety and Environmental Department 20-Apr-2010 07-Mar-2024 New emergency telephone response service provider.

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers. Chemical incident response training.

(+/-)-Propylene oxide

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Legend

CAS - Chemical Abstracts Service	TSCA - United States Toxic Substances Control Act Section 8(b)
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances	Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIOC - New Zealand Inventory of Chemicals
 WEL - Workplace Exposure Limit ACGIH - American Conference of Governmental Industrial Hygienists DNEL - Derived No Effect Level RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic 	 TWA - Time Weighted Average IARC - International Agency for Research on Cancer PNEC - Predicted No Effect Concentration LD50 - Lethal Dose 50% EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative
ICAO/IATA - International Civil Aviation Organization/International Air	IMO/IMDG - International Maritime Organization/International Maritin

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

 $\ensuremath{\text{OECD}}$ - Organisation for Economic Co-operation and Development $\ensuremath{\text{BCF}}$ - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code MARPOL - International Convention for the Prevention of Pollution from Ships ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet