

ALFAA39479

# Nickel(II) octanoate, in mineral spirits

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明:	辛酸镍(II),溶剂油溶液 (8% Ni)
Product Description:	Nickel(II) octanoate, in mineral spirits
Cat No. :	<b>39479</b>
Molecular Formula	C16 H30 NiO4
Supplier	Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific) Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608
Emergency Telephone Number	For information <b>US</b> call: 001-800-227-6701 / <b>Europe</b> call: +32 14 57 52 11 Emergency Number <b>US:</b> 001-201-796-7100 / <b>Europe:</b> +32 14 57 52 99 <b>CHEMTREC</b> Tel. No. <b>US:</b> 001-800-424-9300 / <b>Europe:</b> 001-703-527-3887
E-mail address	begel.sdsdesk@thermofisher.com
Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

## **SECTION 2. HAZARD IDENTIFICATION**

Physical State	Appearance	<b>Odor</b>
Liquid	Green	No information available
or asthma symptoms or breathing difficulties if fertility or the unborn child. Causes damage to	inhaled. May cause genetic defects.	

#### Classification of the substance or mixture

Flammable liquids.	Category 3
Aspiration Toxicity	Category 1
Respiratory Sensitization	Category 1
Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1B
Specific target organ toxicity - (repeated exposure)	Category 1
Acute aquatic toxicity	Category 1
Chronic aquatic toxicity	Category 1

## Label Elements

Nickel(II) octanoate, in mineral spirits



#### Signal Word

Danger

### Hazard Statements

- H226 Flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H317 May cause an allergic skin reaction
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H340 May cause genetic defects
- H350i May cause cancer by inhalation
- H360 May damage fertility or the unborn child
- H372 Causes damage to organs through prolonged or repeated exposure
- H410 Very toxic to aquatic life with long lasting effects

#### **Precautionary Statements**

#### Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P233 Keep container tightly closed
- P240 Ground and bond container and receiving equipment
- P242 Use non-sparking tools
- P243 Take action to prevent static discharges
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P284 In case of inadequate ventilation wear respiratory protection

#### Response

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P308 + P313 IF exposed or concerned: Get medical advice/attention
- P331 Do NOT induce vomiting
- P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor
- P363 Wash contaminated clothing before reuse
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

## Storage

P403 + P235 - Store in a well-ventilated place. Keep cool

## Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Physical and Chemical Hazards

Flammable liquid. Vapors may cause flash fire or explosion.

## Health Hazards

Aspiration hazard if swallowed - can enter lungs and cause damage. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause genetic defects. May cause cancer by inhalation. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

#### **Environmental hazards**

Very toxic to aquatic life with long lasting effects. Is not likely mobile in the environment due its low water solubility. Spillage unlikely to penetrate soil. The product is insoluble and floats on water.

This product does not contain any known or suspected endocrine disruptors. Toxic to terrestrial vertebrates.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Nickel(II) octanoate, in mineral spirits

Component	CAS No	Weight %
2-Ethylhexanoic acid, nickel salt	7580-31-6	48.00
Stoddard solvent	8052-41-3	39.00
2-Ethylhexanoic acid	149-57-5	13.00

## **SECTION 4. FIRST AID MEASURES**

#### General Advice

If symptoms persist, call a physician.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

#### Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

#### Most important symptoms and effects

None reasonably foreseeable. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

#### Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

#### Notes to Physician

Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Powder. Foam. Water may be ineffective. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

#### **Specific Hazards Arising from the Chemical**

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

#### Personal Precautions

#### Nickel(II) octanoate, in mineral spirits

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

#### **Environmental Precautions**

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Should not be released into the environment.

#### Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7. HANDLING AND STORAGE**

#### Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

#### Storage

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

#### Specific Use(s)

Use in laboratories

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

Component	China	Taiwan	Thailand	Hong Kong
2-Ethylhexanoic acid, nickel	-	TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	-
salt				
Stoddard solvent	-	TWA: 100 ppm		TWA: 100 ppm
		TWA: 525 mg/m <sup>3</sup>		TWA: 525 mg/m <sup>3</sup>

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
2-Ethylhexanoic acid, nickel salt		(Vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>	-	
Stoddard solvent	TWA: 100 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 525 mg/m <sup>3</sup> TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> TWA: 350 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup>	-	
2-Ethylhexanoic acid	TWA: 5 mg/m <sup>3</sup>			-	

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH: NIOSH - National Institute for Occupational Safety and Health

#### Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography MDHS42/2 Nickel and inorganic compounds of nickel in air (except nickel carbonyl) Laboratory method using flame atomic absorption spectrometry or electrothermal atomic absorption spectrometry

#### **Exposure Controls**

#### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

#### Personal protective equipment

Eye Protection	Wear safety glasses with side shields (or goggles) (European standard - EN 166)
Hand Protection	Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers	-	EN 374	(minimum requirement)
	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection	Long sleeved clothing
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced <b>Recommended Filter type:</b> Multi-purpose/ABEK conforming to EN14387 low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. <b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.
Environmental exposure controls	Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appeara	nce
Physical	State

Odor Odor Threshold pH Melting Point/Range Softening Point Boiling Point/Range Flash Point No information available No data available No information available No data available No data available No information available 40 °C / 104 °F

Green Liquid

Method - No information available

## Nickel(II) octanoate, in mineral spirits

Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	23 hPa @ 20 °C	
•	No data available	(Air 10)
Vapor Density		(Air = 1.0)
Specific Gravity / Density	0.95 g/cm3	@ 20 °C
Bulk Density	Not applicable	Liquid
Water Solubility	Immiscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/wa	iter)	
Component	log Pow	
Stoddard solvent	6.4	
2-Ethylhexanoic acid	2.7	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
		ovologivo gir/vongur mixtureg poggible
Explosive Properties		explosive air/vapour mixtures possible
Oxidizing Properties	No information available	
Molecular Formula	C16 H30 NiO4	
Molecular Weight	345.10	
morecular mergin	0-0.10	

## SECTION 10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Hazardous Reactions Hazardous Polymerization	None under normal processing. No information available.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition.
Materials to avoid	Oxidizing agent.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nickel oxides.

## SECTION 11. TOXICOLOGICAL INFORMATION

#### Product Information

## (a) acute toxicity;

## Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Stoddard solvent	5000 mg/kg (orl, rat)	LD50 > 3000 mg/kg (Rabbit)	LC50 > 5.5 mg/L (Rat)4 h
2-Ethylhexanoic acid	LD50 = 1600 mg/kg (Rat)	LD50 = 1140 mg/kg(Rabbit)	

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

- (d) respiratory or skin sensitization;
  - RespiratoryCategory 1SkinCategory 1

#### Nickel(II) octanoate, in mineral spirits

May cause sensitization by skin contact

Category 1B (e) germ cell mutagenicity;

(f) carcinogenicity;

Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
2-Ethylhexanoic acid, nickel salt	Carc Cat. 1A			
Stoddard solvent	Carc Cat. 1B			

(g) reproductive toxicity;	Category 1B

- (h) STOT-single exposure; No data available
- (i) STOT-repeated exposure; Category 1
- Central nervous system (CNS). **Target Organs**

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling delayed of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

#### **SECTION 12. ECOLOGICAL INFORMATION**

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic **Ecotoxicity effects** environment. The product contains following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
2-Ethylhexanoic acid	LC50: = 70 mg/L, 96h (Pimephales promelas)	EC50: = 85.4 mg/L, 48h (Daphnia magna)	EC50: = 41 mg/L, 96h (Desmodesmus subspicatus) EC50: = 61 mg/L, 72h (Desmodesmus subspicatus)	EC50 = 110 mg/L 17 h EC50 = 670 mg/L 30 min

Persistence and Degradability	Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Persistence Degradation in sewage treatment plant	Immiscible with water, May persist. Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.
Bioaccumulative Potential	May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
Stoddard solvent	6.4	No data available
2-Ethylhexanoic acid	2.7	No data available

Mobility in soil

Spillage unlikely to penetrate soil The product is insoluble and floats on water Is not likely mobile in the environment due its low water solubility

## Nickel(II) octanoate, in mineral spirits

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential	This product does not contain any known or suspected endocrine disruptors This product does not contain any known or suspected substance This product does not contain any known or suspected substance
	SECTION 13. DISPOSAL CONSIDERATIONS
Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.
	SECTION 14. TRANSPORT INFORMATION
Road and Rail Transport	
UN-No Proper Shipping Name Technical Shipping Name Hazard Class Packing Group	UN1993 Flammable liquid, n.o.s. (Mineral spirits) 3 III
IMDG/IMO	
UN-No Proper Shipping Name Technical Shipping Name Hazard Class Packing Group	UN1993 Flammable liquid, n.o.s. (Mineral spirits) 3 III
IATA	
UN-No Proper Shipping Name Technical Shipping Name Hazard Class Packing Group	UN1993 Flammable liquid, n.o.s. (Mineral spirits) 3 III
Special Precautions for User	No special precautions required

## **SECTION 15. REGULATORY INFORMATION**

## International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL).

	-	List of dangerous	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
	Hazardous Chemicals (2015 Edition)	goods GB 12268 - 2012										
2-Ethylhexanoic acid,	-	-	Х	Х	231-480-1	Х	Х	-	Х	Х	Х	KE-13758

Nickel(II) octanoate, in mineral spirits

nickel salt												
Stoddard solvent	-	Х	Х	Х	232-489-3	Х	Х	Х	-		Х	KE-32199
2-Ethylhexanoic acid	-	-	Х	Х	205-743-6	Х	Х	Х	Х	Х	Х	KE-13740

#### **National Regulations**

## **SECTION 16. OTHER INFORMATION**

Prepared By
Revision Date
Revision Summary

Health, Safety and Environmental Department 09-May-2024 New emergency telephone response service provider.

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

#### Legend

EC50 - Effective Concentration 50%

Dangerous Goods Code

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Ships

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

IMO/IMDG - International Maritime Organization/International Maritime

MARPOL - International Convention for the Prevention of Pollution from

CAS - Chemical Abstracts Service	<b>TSCA</b> - United States Toxic Substances Control Act Section 8(b) Inventory
EINECS/ELINCS - European Inventory of Existing Commercial Chemical	DSL/NDSL - Canadian Domestic Substances List/Non-Domestic
Substances/EU List of Notified Chemical Substances	Substances List
PICCS - Philippines Inventory of Chemicals and Chemical Substances	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	AICS - Australian Inventory of Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances	NZIOC - New Zealand Inventory of Chemicals
WEL - Workplace Exposure Limit	TWA - Time Weighted Average
ACGIH - American Conference of Governmental Industrial Hygienists	IARC - International Agency for Research on Cancer
DNEL - Derived No Effect Level	PNEC - Predicted No Effect Concentration
RPE - Respiratory Protective Equipment	LD50 - Lethal Dose 50%

**RPE** - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association** ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development BCF - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Disclaimer

data

### Nickel(II) octanoate, in mineral spirits

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## End of Safety Data Sheet