

SCIENTIFIC

ALFAA41311

## Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

**SAFETY DATA SHEET** 

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明:	异丙醇钐(III)
Product Description:	Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol
Cat No. :	<b>41311</b>
Molecular Formula	C9 H21 O3 Sm
Supplier	Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific) Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608
Emergency Telephone Number	For information <b>US</b> call: 001-800-227-6701 / <b>Europe</b> call: +32 14 57 52 11 Emergency Number <b>US:</b> 001-201-796-7100 / <b>Europe:</b> +32 14 57 52 99 <b>CHEMTREC</b> Tel. No. <b>US:</b> 001-800-424-9300 / <b>Europe:</b> 001-703-527-3887
E-mail address	begel.sdsdesk@thermofisher.com
Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

## **SECTION 2. HAZARD IDENTIFICATION**

Physical State	
Liquid	

Appearance No information available

Odor No information available

## **Emergency Overview**

Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness and dizziness. Toxic to aquatic life. Harmful to aquatic life with long lasting effects. May cause damage to organs through prolonged or repeated exposure. Moisture sensitive.

## Classification of the substance or mixture

Flammable liquids.	Category 2
Aspiration Toxicity	Category 1
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Specific target organ toxicity - (repeated exposure)	Category 2
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 3

## Label Elements

Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol



## Signal Word

Danger

## Hazard Statements

- H225 Highly flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness
- H401 Toxic to aquatic life
- H412 Harmful to aquatic life with long lasting effects
- H373 May cause damage to organs through prolonged or repeated exposure
- H361 Suspected of damaging fertility or the unborn child

## **Precautionary Statements**

#### Prevention

- P201 Obtain special instructions before use
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear eye protection/ face protection
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P240 Ground and bond container and receiving equipment
- P242 Use non-sparking tools
- P243 Take action to prevent static discharges

#### Response

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P331 Do NOT induce vomiting
- P332 + P313 If skin irritation occurs: Get medical advice/attention
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

- P308 + P313 IF exposed or concerned: Get medical advice/attention
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
- P362 + P364 Take off contaminated clothing and wash it before reuse

## Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

## Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Physical and Chemical Hazards

Vapors may cause flash fire or explosion. Highly flammable.

## Health Hazards

Aspiration hazard if swallowed - can enter lungs and cause damage. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

#### **Environmental hazards**

Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Is not likely mobile in the environment due its low water solubility. Spillage unlikely to penetrate soil.

Toxic to terrestrial vertebrates. This product does not contain any known or suspected endocrine disruptors.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

Component	CAS No	Weight %
Toluene	108-88-3	47.50
Isopropyl alcohol	67-63-0	47.50
Samarium(III) isopropoxide in ampoules	3504-40-3	5.00

## **SECTION 4. FIRST AID MEASURES**

#### General Advice

If symptoms persist, call a physician.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

#### Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

#### Most important symptoms and effects

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

## Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

#### Notes to Physician

Treat symptomatically. Symptoms may be delayed.

## **SECTION 5. FIRE-FIGHTING MEASURES**

#### **Suitable Extinguishing Media**

Water mist may be used to cool closed containers.

## Extinguishing media which must not be used for safety reasons

No information available.

#### Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

## **Personal Precautions**

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

## Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

#### **Environmental Precautions**

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

### Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7. HANDLING AND STORAGE

#### Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### Storage

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

#### Specific Use(s)

Use in laboratories

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Control Parameters**

Component	China	Taiwan	Thailand	Hong Kong
Toluene	TWA: 50 mg/m <sup>3</sup> STEL: 100 mg/m <sup>3</sup> Skin	TWA: 100 ppm TWA: 376 mg/m <sup>3</sup>	Ceiling: 300 ppm STEL: 500 ppm TWA: 200 ppm	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup>
Isopropyl alcohol	TWA: 350 mg/m <sup>3</sup> STEL: 700 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 983 mg/m <sup>3</sup>	TWA: 400 ppm	TWA: 400 ppm TWA: 983 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1230 mg/m <sup>3</sup>

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Toluene	TWA: 20 ppm	(Vacated) TWA: 100	IDLH: 500 ppm	STEL: 100 ppm 15 min	TWA: 50 ppm (8hr)
		ppm	TWA: 100 ppm	STEL: 384 mg/m <sup>3</sup> 15	TWA: 192 mg/m <sup>3</sup> (8hr)
		(Vacated) TWA: 375	TWA: 375 mg/m <sup>3</sup>	min	STEL: 100 ppm
		mg/m³	STEL: 150 ppm	TWA: 50 ppm 8 hr	(15min)
		Ceiling: 300 ppm	STEL: 560 mg/m <sup>3</sup>	TWA: 191 mg/m <sup>3</sup> 8 hr	STEL: 384 mg/m <sup>3</sup>
		(Vacated) STEL: 150		Skin	(15min)
		ppm			Skin
		(Vacated) STEL: 560			
		mg/m³			
		TWA: 200 ppm			
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400	IDLH: 2000 ppm	STEL: 500 ppm 15 min	
	STEL: 400 ppm	ppm	TWA: 400 ppm	STEL: 1250 mg/m <sup>3</sup> 15	
		(Vacated) TWA: 980	TWA: 980 mg/m <sup>3</sup>	min	
		mg/m <sup>3</sup>	STEL: 500 ppm	TWA: 400 ppm 8 hr	
		(Vacated) STEL: 500	STEL: 1225 mg/m <sup>3</sup>	TWA: 999 mg/m <sup>3</sup> 8 hr	
		ppm			
		(Vacated) STEL: 1225			
		mg/m <sup>3</sup>			
		TWA: 400 ppm			
		TWA: 980 mg/m <sup>3</sup>			

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists

## Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

OSHA - Occupational Safety and Health Administration NIOSH: NIOSH - National Institute for Occupational Safety and Health

### Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry MDHS 99 Metals in air by ICP-AES

### **Exposure Controls**

## **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

#### Personal protective equipment

Eye Protection	Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection	Long sleeved clothing
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced <b>Recommended Filter type:</b> low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. <b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.
Environmental exposure controls	Prevent product from entering drains. Do not allow material to contaminate ground water system.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

## Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

Appearance Physical State	Liquid	
Odor	No information available	
Odor Threshold	No data available	
pH Molting Point/Pongo	No information available No data available	
Melting Point/Range Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	4 °C / 39.2 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	1
·		
Vapor Pressure	23 hPa @ 20 °C	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	No data available	
Bulk Density	Not applicable	Liquid
Water Solubility	Immiscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/wat	•	
Component	log Pow	
Toluene	2.73	
Isopropyl alcohol	0.05 No data available	
Autoignition Temperature	No data available	
Decomposition Temperature Viscosity	No data available	
Explosive Properties	NO data avaliable	Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	vapors may form explosive mixtures with an
Charling Fropenies		
Melecular Formula	C9 H21 O3 Sm	
Molecular Formula	327.50	
Molecular Weight	327.30	

## SECTION 10. STABILITY AND REACTIVITY

Stability	Moisture sensitive.
Hazardous Reactions Hazardous Polymerization	None under normal processing. No information available.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition.
Materials to avoid	Strong bases.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Samarium oxide.

## SECTION 11. TOXICOLOGICAL INFORMATION

## **Product Information**

## (a) acute toxicity; Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat)1 h
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat)4 h

## Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

(b) skin corrosion/irritation;	Category 2
(c) serious eye damage/irritation;	Category 2
(d) respiratory or skin sensitization; Respiratory Skin	No data available No data available
(e) germ cell mutagenicity;	No data available
(f) carcinogenicity;	No data available
	There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	Category 2
(h) STOT-single exposure;	Category 3
Results / Target organs	Central nervous system (CNS)
(i) STOT-repeated exposure;	Category 2
Target Organs	Neuropsychological effects, Eyes, Ears.
(j) aspiration hazard;	Category 1
Symptoms / effects,both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
	SECTION 12. ECOLOGICAL INFORMATION

## **Ecotoxicity effects**

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Toluene	5-7 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	static	EC50 = 19.7 mg/L 30 min
Isopropyl alcohol	flow-through	h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min

ALFAA41311

# SAFETY DATA SHEET

## Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

Persistence and Degradability	Product contains heavy metals. Discharge into the environment must be avoided. Spec				
Develotorios	pre-treatment is necessary				
Persistence	Immiscible with water, May persis	Degradability			
Compo Tolue			Degradability 86% (20d)		
108-88-3	(47.50)		× 7		
Degradation in sewage treatment plant	Contains substances known to be water treatment plants.	substances known to be hazardous to the environment or not degradable in w tment plants.			
Bioaccumulative Potential	May have some potential to bioac	cumulate; Pro	oduct has a high potential to bioconcentrate		
Component	log Pow		Bioconcentration factor (BCF)		
Toluene	2.73		90		
Isopropyl alcohol	0.05		No data available		
Mobility in soil	solubility	-	nobile in the environment due its low water		
Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential	This product does not contain any known or suspected endocrine disruptors This product does not contain any known or suspected substance This product does not contain any known or suspected substance				
	SECTION 13. DISPOSAL CO	NSIDERATI	ONS		
Waste from Residues/Unused Products	Waste is classified as hazardous. on waste and hazardous waste. D		accordance with the European Directives accordance with local regulations.		
Contaminated Packaging	retain product residue, (liquid and	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.			
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.				
	SECTION 14. TRANSPORT	INFORMAT	ION		
Road and Rail Transport					
UN-No Proper Shipping Name Technical Shipping Name Hazard Class Subsidiary Hazard Class Packing Group	UN3274 ALCOHOLATES SOLUTION, N.O.S. (Samarium(III) isopropoxide, TOLUENE) 3 8 II				
IMDG/IMO					

IM	DG/	IMC	)

UN-No	UN3274
Proper Shipping Name	ALCOHOLATES SOLUTION, N.O.S.
Technical Shipping Name	(Samarium(III) isopropoxide, TOLUENE)
Hazard Class	3
Subsidiary Hazard Class	8
Packing Group	II

<u>IATA</u>

UN-No

UN3274

## Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

Proper Shipping Name	ALCOHOLATES SOLUTION, N.O.S.	
Technical Shipping Name	(Samarium(III) isopropoxide, TOLUENE)	
Hazard Class	3	
Subsidiary Hazard Class	8	
Packing Group	II	
Special Precautions for User	No special precautions required	

## **SECTION 15. REGULATORY INFORMATION**

#### International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The Inventory of Hazardous Chemicals (2015 Edition)	List of dangerous goods GB 12268 - 2012	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
Toluene	Х	Х	Х	Х	203-625-9	Х	Х	Х	Х	Х	Х	KE-33936
Isopropyl alcohol	Х	Х	Х	Х	200-661-7	Х	Х	Х	Х	Х	Х	KE-29363
Samarium(III) isopropoxide in ampoules	-	-	Х	-	-	-	-	-	-		-	-

#### **National Regulations**

## **SECTION 16. OTHER INFORMATION**

**Prepared By Revision Date Revision Summary** 

Health, Safety and Environmental Department 09-May-2024 New emergency telephone response service provider.

### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

#### Legend

CAS - Chemical Abstracts Service	<b>TSCA</b> - United States Toxic Substances Control Act Section 8(b) Inventory
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances	
WEL - Workplace Exposure Limit ACGIH - American Conference of Governmental Industrial Hygienists DNEL - Derived No Effect Level RPE - Respiratory Protective Equipment	TWA - Time Weighted Average IARC - International Agency for Research on Cancer PNEC - Predicted No Effect Concentration LD50 - Lethal Dose 50%

LC50 - Lethal Concentration 50%

EC50 - Effective Concentration 50%

**SAFETY DATA SHEET** 

Samarium(III) isopropoxide, 99% (REO), 5% w/v in toluene/isopropanol

POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

NOEC - No Observed Effect Concentration
<b>PBT</b> - Persistent, Bioaccumulative, Toxic

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road OECD - Organisation for Economic Co-operation and Development BCF - Bioconcentration factor	<ul> <li>IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code</li> <li>MARPOL - International Convention for the Prevention of Pollution from Ships</li> <li>ATE - Acute Toxicity Estimate</li> <li>VOC - (Volatile Organic Compound)</li> </ul>
Key literature references and sources for data https://echa.europa.eu/information-on-chemicals Suppliers safety data sheet, Chemadvisor - LOLI, Merck index,	RTECS

Physical hazards	
Health Hazards	
Environmental hazards	

On basis of test data Calculation method Calculation method

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**