

Portavo 907 Multi pH

Portable multiparameter analyzer for all Memosens pH/ORP, conductivity, and oxygen sensors, and all analog pH/ORP electrodes.



Great Flexibility Thanks to Multiparameter Technology

Portavo 907 Multi pH enables versatile and flexible use. In combination with digital Memosens sensors, the following process variables are supported:

- pH
- ORP
- Contacting conductivity
- Toroidal conductivity
- Amperometric oxygen
- Optical oxygen
- Temperature

As soon as the Memosens sensor is connected, the Portavo 907 Multi pH automatically adjusts to the selected parameter. All relevant sensor data can be seen at a glance.

Analog pH/ORP sensors can also still be used, if required.

Comprehensive Data Logger

The following logger types can be selected:

- Manual logging
- Time-controlled logging at set intervals
- Signal-controlled logging of process variables and temperatures
- Combined time- and signal-controlled logging
- Threshold-controlled logging with pre-trigger

The data logger for up to 10,000 entries records the measuring point, annotation, sensor ID, sensor serial number (Memosens), primary value, temperature, time stamp, and device status.

User-Friendly Software

Portavo 907 Multi pH proves that high functionality and ease of use do not exclude one another.

It guides you step by step through the calibration procedure. Technical terms are clearly explained in the context help.

Portavo 907 features a wide range of new functions, such as

- a new pH calibration procedure with a set process flow
- multi-level user management with access control
- direct assignment of Memosens sensors to device for increased safety during operation

Multi-Channel Function for Simultaneous Operation of 2 Sensors


If equipped with the multi-channel option, Portavo 907 Multi pH can be used for simultaneous measurements using 2 flexibly combined sensors. The multi-channel function is added to the functionality of the data logger.

Portavo



Facts and Features

- High-resolution color graphic display
- Transflective, even when exposed to direct sunlight
- Mineral glass screen can still be read perfectly after many years
- Micro USB port and Paraly SW 112 operating software
- Sensor quiver protects the sensor from drying out and damage
- pH calibration with set process flow
- Temperature offset
- High-performance polymer housing is waterproof with IP67 / IP66 protection and ensures high impact resistance
- Intelligent data logger with 10,000 entries and graphic display
- Memosens sensors and analog pH/ORP sensors
- Multi-channel function
- Li-ion rechargeable battery
 - USB chargeable
- Concentration measurement with toroidal conductivity sensors



Specifications

pH/mV input (analog)	pH socket DIN 19 262 (13/4 mm)		
	pH measuring range	-2 ... +16	
	Decimal places ^{*)}	2 or 3	
	Input resistance	1 x 10 ¹² Ω (0 ... +35 °C/+32 ... +95 °F)	
	Input current	1 x 10 ⁻¹² A (at RT, doubles every 10 K)	
	Measuring cycle	Approx. 1 s	
	Measurement error ^{1,2,3)}	< 0.01 pH, TC < 0.001 pH/K	
	mV measuring range	-1300 ... +1300 mV	
	Measuring cycle	Approx. 1 s	
	Measurement error ^{1,2,3)}	< 0.1 % meas. val. + 0.3 TC < 0.03 mV/K mV	
Temperature input	2 x Ø 4 mm for integrated or separate temperature probe		
	Measuring ranges	NTC 30 kΩ -20 ... +120 °C / -4 ... +248 °F	
		Pt1000 -40 ... +250 °C / -40 ... +482 °F	
	Measuring cycle	Approx. 1 s	
	Measurement error ^{1,2,3)}	< 0.2 K (Tamb = +23 °C / +73.4 °F); TC < 25 ppm/K	
Memosens pH input (also ISFET)	M8 socket, 4-pin, for Memosens laboratory cable		
	Display ranges ⁴⁾	pH -2.000 ... +16.000	
	Sensor adjustment ^{*)}	pH calibration	
	Operating modes ^{*)}	Calimatic	Calibration with automatic buffer recognition
		Manual	Manual calibration with entry of individual buffer values
		Data entry	Data entry of zero point and slope
	Calimatic buffer sets ^{*)}	-01- Mettler-Toledo	2.00/4.01/7.00/9.21
		-02- Knick CaliMat	2.00/4.00/7.00/9.00/12.00
		-03- Ciba (94)	2.06/4.00/7.00/10.00
		-04- NIST Technical	1.68/4.00/7.00/10.01/12.46
-05- NIST Standard		1.679/4.006/6.865/9.180	
-06- HACH		4.01/7.00/10.01/12.00	
-07- WTW techn. buffers		2.00/4.01/7.00/10.00	
-08- Hamilton		2.00/4.01/7.00/10.01/12.00	
-09- Reagecon		2.00/4.00/7.00/9.00/12.00	
-10- DIN 19267		1.09/4.65/6.79/9.23/12.75	
-U1- (User)	Chargeable via Paraly SW 112		
Permissible calibration range	Zero point	6 ... 8 pH	
	Slope (Sensoface may indicate restrictions)	Approx. 74 ... 104 %	
Calibration timer ^{*)}	Interval 1 ... 99 days, can be switched off		
Sensoface	Provides information on the condition of the sensor		
Evaluation of	Zero point/slope, response time, calibration interval		

Portavo

Specifications

Memosens ORP input	M8 socket, 4-pin, for Memosens laboratory cable		
	Display ranges ⁴⁾	mV	-2000 ... +2000 mV
		Temperature	-50 ... +250 °C -58 ... +482 °F
	Sensor adjustment ^{*)}	ORP calibration (zero offset)	
Permissible calibration range	ΔmV (offset)	-700 ... +700 mV	
Memosens conductivity input	M8 socket, 4-pin, for Memosens laboratory cable		
	Measuring range	Sensor SE 615/1-MS	10 μS/cm ... 20 mS/cm
	Measuring cycle	Approx. 1 s	
	Temperature compensation	Linear 0 ... 20 %/K, adjustable reference temperature nLF: 0 ... +120 °C/+32 ... +248 °F NaCl HCl (ultrapure water with traces) NH3 (ultrapure water with traces) NaOH (ultrapure water with traces)	
	Conductivity	0.001 μS/cm	(c < 0.05 cm ⁻¹)
		0.01 μS/cm	(c = 0.05 ... 0.2 cm ⁻¹)
Resistivity	0.1 μS/cm	(c > 0.2 cm ⁻¹)	
	00.00 ... 99.99 MΩ • cm		
Salinity	0.0 ... 45.0 g/kg	(0 ... +30 °C) (+32 ... +86 °F)	
	TDS	0 ... 1999 mg/l	(+10 ... +40 °C) (+50 ... +104 °F)
Concentration	0.00 ... 100 wt%		
Concentration determination	NaCl	0 – 26 wt% (0 °C / +32 °F) ... 0 – 28 wt% (+100 °C / +212 °F)	
	HCl	0 – 18 wt% (-20 °C / -4 °F) ... 0 – 18 wt% (+50 °C / +122 °F)	
	NaOH	0 – 13 wt% (0 °C / +32 °F) ... 0 – 24 wt% (+100 °C / +212 °F)	
	H ₂ SO ₄	0 – 26 wt% (-17 °C / -1.4 °F) ... 0 – 37 wt% (+110 °C / +230 °F)	
	HNO ₃	0 – 30 wt% (-20 °C / -4 °F) ... 0 – 30 wt% (+50 °C / +122 °F)	
	H ₂ SO ₄	94 – 99 wt% (-17 °C / -1.4 °F) ... 89 – 99 wt% (+115 °C / +239 °F)	
	HCl	22 – 39 wt% (-20 °C / -4 °F) ... 22 – 39 wt% (+50 °C / +122 °F)	
	HNO ₃	35 – 96 wt% (-20 °C / -4 °F) ... 35 – 96 wt% (+50 °C / +122 °F)	
H ₂ SO ₄	28 – 88 wt% (-17 °C / -1.4 °F) ... 39 – 88 wt% (+115 °C / +239 °F)		
	NaOH	15 – 50 wt% (0 °C / +32 °F) ... 35 – 50 wt% (+100 °C / +212 °F)	
Sensor adjustment	Cell constant	Input of cell constant with simultaneous display of conductivity value and temperature	
	Solution input	Input of calibration solution conductivity with simultaneous display of cell constant and temperature	
	Auto	Automatic determination of cell constant with KCl or NaCl solution	
Temperature probe	Temperature adjustment (offset) with Memosens sensors		

Specifications

Memosens input Amperometric oxygen	M8 socket, 4-pin, for Memosens laboratory cable Display ranges ⁴⁾ Saturation Concentration Partial pressure Temperature range ⁴⁾	0.000 ... 200.0 % 000 µg/l ... 20.00 mg/l 0.0... 1000 mbar -20 ... +150 °C / -4 ... +302 °F
Sensor adjustment	Automatic calibration in air, adjustable relative humidity Zero calibration	
Temperature probe	Temperature adjustment (offset) with Memosens sensors Storage In quiver	
Connections	2 x socket Ø 4 mm for separate temperature probe 1 x M8 socket, 4-pin, for Memosens laboratory cable 1 x micro USB-B for data transmission to PC 1 x pH socket in acc. with DIN 19262	
Device operation	Easy-to-use menu navigation with graphic symbols and detailed user hints in plain text	
Languages	German, English, French, Spanish, Italian, Portuguese	
Status indicators	For battery condition, logger	
Graphic display	QVGA TFT display with white backlighting	
Keypad	[on/off], [meas], [enter], [◀], [▶], [▲], [▼] 2 softkeys with context-dependent assignment	
Data logger	Space for 10,000 entries Recording Manual, interval- and/or event-controlled with limit value and pre-trigger, management of tag numbers and annotations	
MemoLog calibration data logger (Memosens only)	Can save up to 100 Memosens calibration records Recording Directly readable via MemoSuite or Paraly SW 112 (USB) Can be shown on the display Manufacturer, sensor type, serial no., zero point, slope, calibration date	
Communication	USB 2.0 Profile Usage HID, driverless installation Data transfer and configuration via the Paraly SW 112 software Printer interface	
Diagnostic functions	Sensor data (Memosens only) Calibration data Device self-test Device data Manufacturer, sensor type, serial number, wear, operating time Calibration date, zero point, slope Automatic memory test (FLASH, EEPROM, RAM) Device type, software version, hardware version	
Data retention	Parameter, calibration data > 10 years	
EMC	EN 61326-1 (General requirements) Emitted interference Interference immunity EN 61326-2-3 (Particular requirements for transducers) Class B (residential) Industrial applications	

Portavo

Specifications

RoHS conformity	According to Directive 2011/65/EU	
Power supply	4 x AA (Mignon) alkaline batteries 4 x NiMH rechargeable batteries or 1 x Li-ion rechargeable battery (rechargeable via USB)	
Rated operating conditions	Ambient temperature	-10 ... +55 °C / +14 ... +131 °F
	Transport/Storage temperature	-25 ... +70 °C / -13 ... +158 °F
	Relative humidity	0 ... 95 %, brief condensation permissible
Housing	Material	PA12 GF30 + TPE
	Protection	IP 66/67 with pressure compensation
	Dimensions	Approx. 132 x 156 x 30 mm / 5.2 x 6.14 x 1.18 inches
	Weight	Approx. 500 g / 1.10 lbs

*) User-defined

1) At rated operating conditions

2) ± 1 digit

3) Plus sensor error

4) Ranges dependent on Memosens sensor


5) c = cell constant

Portavo 907 Multi pH Product Line

Portavo 907 Multi pH		Order no.
	<p>Portavo 907 Multi pH for measurement using digital Memosens sensors for pH/ORP, conductivity (contacting or toroidal), and oxygen or using the SE 340 optical oxygen sensor, incl. Paraly SW 112 configuration software with USB connector cable and USB adapter (A female to B male) for printer connection.</p>	<p>Portavo 907 Multi pH</p>
<p>Portavo 907 SET-MULTI-PH</p>		
	<p>Portavo 907 Multi pH, SE 102-MS Memosens pH sensor, CA/MS-001XFA-L cable, ZU 0934 field case, USB connector cable, CS-PSET47 CaliMat buffer set</p>	<p>907SET-MULTI-PH</p>
<p>Portavo 907 SET-MULTI-PH-101</p>		
	<p>Portavo 907 Multi pH, SE 101-MS Memosens pH sensor, CA/MS-001XFA-L cable, USB connector cable, ZU 0934 field case, CS-PSET479 CaliMat buffer set</p>	<p>907SET-MULTI-PH-101</p>
<p>pH/Pt1000 sensor</p>		
	<p>Digital Memosens pH sensor Polymer body, ceramic junction, length 120 mm / 4.72 inches</p>	<p>SE 101 MS</p>
<p>pH/Pt1000 sensor</p>		
	<p>Digital Memosens pH sensor Glass body, ceramic junction, length 110 mm / 4.33 inches</p>	<p>SE 102 MS</p>
<p>pH/Pt1000 sensor</p>		
	<p>Digital Memosens pH puncture sensor Polymer body, length 90 mm / 2.36 inches</p>	<p>SE 104 MS</p>

Portavo

Portavo 907 Multi pH Product Line

		Order no.
2-electrode sensor		
	Digital conductivity sensor with Memosens technology Stainless steel body, length 120 mm / 4.72 inches	SE 202-MS
2-electrode sensor		
	Digital conductivity sensor with Memosens technology Polymer body, length 120 mm / 4.72 inches	SE 615/1-MS
Toroidal conductivity sensor (digital)		
	with dairy pipe DN 50 process connection	SE 680N-C1N4U00M
	with Varivent DN 50 process connection	SE 680N-V1N4U00M
	with 2" clamp process connection	SE 680N-J2N4U00M
	with process connection for für ARF 210/215	SE 680N-K8N4U00M
Oxygen sensor		
	The SE 715 oxygen sensor with Memosens plug-in system requires little maintenance and is equipped with a temperature probe. It features high long-term stability, a fast response, and low flow dependence. The sensor is designed for the simultaneous measurement of dissolved oxygen and temperature.	SE 715 MS
Optical oxygen sensor		
	Thanks to its optical measuring function and digital data transmission, the SE 340 oxygen sensor is ideal for use with the Portavo 907. It is sturdy and waterproof (IP 68), and, with its extremely fast response time, suitable for a wide range of applications. A further plus point is the beveled membrane, which is both free from incident flow and easy to clean. With a 1.5 m / 4.92 ft fixed cable.	SE 340
Memosens cable		
	Measuring cable for digital sensors with Memosens connector Length 1.5 m / 4.92 ft	CA/MS-001XFA-L
	Measuring cable for digital sensors with Memosens connector Length 2.9 m / 9.51 ft	CA/MS-003XFA-L
	Measuring cable for digital sensors with M12 socket, 4-pin, M8 connector, 4-pin, length 1.5 m / 4.92 ft	CA/M12-001M8-L
Adapter		
	Adapter for 12 mm / 0.47 inch industrial sensors with PG 13.5 thread.	ZU 0939

Portavo 907 Multi pH Product Line

pH/Pt1000 sensor



Polymer body, fiber junction, length 120 mm / 4.72 inches

Order no.

SE 101 AN

pH/Pt1000 sensor



Glass body, ceramic junction, length 110 mm / 4.33 inches

SE 102 AN


pH puncture sensor



Polymer body, hole junction,
length 65 / 25 mm, 4.33 / 0.98 inches

SE 104 AN

Sensor quiver



5 pcs., replacement, for leak-proof storage of sensors

ZU 0929

Sturdy field case



For device and sensor

ZU 0934

Li-ion rechargeable battery



Li-ion rechargeable battery (USB chargeable with Portavo
904, 907, and 908 only)

ZU 0925

pH/Pt1000 sensor







For measurements in Ex Zone 0, including equipotential bonding
cable, glass body, ceramic junction, length 105 mm / 4.13 inches

ZU 6979






Portavo

Portavo 907 Multi pH Product Line

Pt1000 temperature probe	Order no.
 <p>For temperature measurements with quick response time: Monel 2.4360, -10 ... +100 °C/+14 ... +212 °F, accuracy class A according to DIN IEC 751</p>	ZU 6959
<p>Base stand</p>  <p>Base stand for accepting up to 3 sensors with base plate made of stainless steel</p>	ZU 6953
<p>TAN Options</p>  <p>Cal SOP calibration method: User management, sensor check, temperature adjustment (offset)</p> <p>Temperature adjustment (offset)</p> <p>Multi-channel function</p>	<p>SW-P001</p> <p>SW-P002</p> <p>SW-P003</p>
<p>Software</p>  <p>PC software for configuration and firmware update (free download at www.knick.de)</p>	

Portavo 907 Multi pH Product Line

CaliMat pH Buffer Solutions

		Quantity	Order no.
	pH 2.00 (20 °C / 68 °F)	250 ml	CS-P0200/250
	pH 4.00 (20 °C / 68 °F)	250 ml	CS-P0400/250
		1000 ml	CS-P0400/1000
	pH 7.00 (20 °C / 68 °F)	250 ml	CS-P0700/250
		1000 ml	CS-P0700/1000
	pH 9.00 (20 °C / 68 °F)	250 ml	CS-P0900/250
		1000 ml	CS-P0900/1000
	pH 12.00 (20 °C / 68 °F)	250 ml	CS-P1200/250

Portavo

Portavo 907 Multi pH Product Line

CaliMat pH Buffer Solutions

	Quantity	Order no.
 <p>Set pH 4.00 (20 °C / 68 °F)</p>	3 x 250 ml	CS-PSET4
 <p>Set pH 7.00 (20 °C / 68 °F)</p>	3 x 250 ml	CS-PSET7
 <p>Set pH 9.00 (20 °C / 68 °F)</p>	3 x 250 ml	CS-PSET9
 <p>Set pH 4.00 / 7.00 / 9.00 (20 °C / 68 °F)</p>	3 x 250 ml	CS-PSET479
 <p>KCl solution, 3 molar</p>	250 ml	ZU 0062

Authorised distributor

In Australia:

For customer service, call 1300-735-292

To email an order, ordersau@thermofisher.com

To order online: thermofisher.com

In New Zealand:

For customer service, call 0800-933-966

To email an order, ordersnz@thermofisher.com

To order online: thermofisher.com