



cerillo

stratus

miniaturized plate reader



Features

-  Functional in a broad range of environments, including anaerobic chambers, on shakers, remote field settings, and in heated and humidified incubators
-  Continuous real-time measurements of optical density at user-determined time intervals
-  Fits 6, 12, and 96-well plates
-  User-friendly software that exports data to any spreadsheet software
-  Single mode (absorbance) and single wavelength only. Available in standard 600 nm or customized wavelengths
- 

Small footprint and stackable

Available products

Name	SKU
Stratus, 600nm	R2600
Stratus, 496nm	R2496
Stratus, 650nm	R2650
Stratus, Adapter	R2APT



Uniquely small footprint allows for usage and storage in confined spaces



Sturdy design allows for use in restrictive environments like incubators and anaerobic chambers



Reasonably priced with no annual subscriptions or charges for software updates



User-friendly flexible interface allows for use with or without a computer

**the stratus is
uniquely designed
for microbial growth
curve measurements**

All Cerillo products are for research use only and are not intended for use in diagnostic procedures. T

Authorised distributor

In Australia:

For customer service, call 1300-735-292
To email an order, ordersanz@thermofisher.com
To order online: thermofisher.com

In New Zealand:

For customer service, call 0800-933-966
To email an order, ordersanz@thermofisher.com
To order online: thermofisher.com

ThermoFisher
SCIENTIFIC