

Process Raman analysis

# MarqMetrix 0.25 in. Process BallProbe Sampling Optic

0.25 in. diameter for demanding laboratory and process applications, with TouchRaman Immersion Technology

## Designed for harsh environments

The Thermo Scientific™ MarqMetrix™ 0.25 in. Process BallProbe™ Sampling Optic is our most robust TouchRaman™ immersion contact probe. This 0.25 in. (6.3mm) diameter Hastelloy C-276 probe features a gold-compression seal with a pressure design condition of 6,000psi, allowing the probe to be used in extremely challenging chemical, pressure, and temperature conditions.

The use of corrosion resistant Hastelloy C-276, gold, and sapphire as the only wetted materials allow the MarqMetrix 0.25 in. Process BallProbe Sampling Optic to withstand the harshest chemical environments.

## Simply touch & measure

MarqMetrix BallProbe technology utilizes an exclusively sourced, high-grade spherical sapphire lens. The short focal length of the spherical optic allows for TouchRaman Immersion Technology —where users simply touch the probe to the sample—yielding highly reproducible sampling of liquids, solids, slurries, powders and heterogeneous mixtures.

The simplicity of design is especially important in process applications where measurement accuracy and reproducibility are mission critical.

Users simply touch the probe to the sample — yielding highly reproducible sampling

## Features and benefits

- Immersion contact probe for touch measurements
- Measures liquids, solids, slurries, powders, and heterogeneous mixtures
- Simple design for measurement accuracy and reproducibility
- Designed to withstand challenging chemical, pressure, and temperature conditions

## Applications

- Biopharmaceutical manufacturing
- Pharmaceutical manufacturing
- Food and beverage processing
- Polymer and plastic manufacturing
- Hazardous chemical applications



The curvature of the UV-grade sapphire ball facilitates material exchange near the surface of the lens, preventing the buildup of materials that interfere with spectral acquisition.

The form factor and 'self-cleaning' properties make the MarqMetrix 0.25 in. Process BallProbe Sampling Optic an ideal choice for process flow applications.

The utility of the MarqMetrix 0.25 in. Process BallProbe Sampling Optic is optimized when paired with the Thermo Scientific™ MarqMetrix™ Fiber BallProbe™ Sampling Optic—a complete sampling solution for accurate and repeatable Raman measurements. However, any BallProbe can be purchased as a standalone product for use with existing probes or open-optic configurations.



Wetted materials	
<b>Probe body</b>	0.25 in. (6.3mm) OD Hastelloy C-276
<b>Immersion optics</b>	5.00mm diameter UV-grade sapphire ball
<b>Sealing materials</b>	Gold

Optical properties	
Made with high purity UV-grade sapphire ball lens aligned along the C-axis, eliminating response variability due to birefringence	

Operating conditions	
Suitable for continuous exposure to dilute and concentrated acids (hot & cold), bases and most organic solvents including ethanol, THF, ethyl acetate, acetone, DCM, toluene, pentane and acetonitrile	

Related products	
Thermo Scientific™ MarqMetrix™ All-In-One Process Raman Analyzer	
Thermo Scientific™ MarqMetrix™ Performance BallProbe™ Sampling Optic	
Thermo Scientific™ MarqMetrix™ Fiber BallProbe™ Sampling Optic filtered fiber optic interface specifically designed for the MarqMetrix BallProbe and MarqMetrix All-In-One Process Raman Analyzer	
Thermo Scientific™ MarqMetrix™ Proximal Probe Sampling Optic	

Specifications	
<b>Probe immersion length</b>	4 in. (102mm)
<b>Probe OD (Outside Diameter)</b>	0.25 in. (6.3mm)
<b>Sample working distance</b>	TouchRaman (Sample contacts BallProbe lens)
<b>Continuous operating temperature range</b>	-20°C to 300°C
<b>Pressured design condition</b>	6,000psi (413 bar)
<b>Compatible wavelengths</b>	500-1100nm



Learn more at [thermofisher.com/marqmetrixAIO](https://thermofisher.com/marqmetrixAIO)

**thermo** scientific