

## Gallery Plus discrete, photometric analyzer

Fully automated, sample oriented, random access analyzer

Thermo Scientific™ Gallery™ Plus is a fully automated, sample oriented random access analyzer. Many different tests can be run simultaneously from a single sample. Panels of system applications are predefined into the analyzer, e.g., for food, beverage, water, environmental and bioprocess quality control and testing. However, new user-specific applications can be defined.

Gallery Plus employs colorimetric end-point and kinetic as well as turbidimetric and bichromatic reactions with or without sample blanking. System supports automated standard addition measurement method for complex sample matrices.

Optional electrochemical (ECM) unit uses ion selective electrodes for pH measurement. The ECM unit can also measure conductivity.

### Measurement

Single channel interference filter photometer with beam splitting reference, 12 filter positions.

<b>Filter range:</b>	340 - 880 nm
<b>Incubation temperature:</b>	Controlled at 25 - 60 °C, no cooling - preset to 37 °C
<b>Light source:</b>	Xenon flash lamp
<b>Absorbance range:</b>	0 - 3.5 A - resolution of 0.001 A - reproducibility of SD <0.005 A at 2 A

### Reaction vessels

Discrete disposable cuvette. Continuous access to cuvettes without interrupting test processing.

<b>On-Board Capacity:</b>	360 measurement cells - 36 cuvettes with 10 reaction cells - 1 to 3 hour walk-away time depending on workload
<b>Reaction End Volume:</b>	120 - 300 µL

### Samples

Continuous access to samples without interrupting test processing. Automatic identification via internal barcode reader.

<b>On-Board Capacity:</b>	up to 108 samples - 9 or 18-position sample rack - max 6 racks
<b>Sample Volumes:</b>	2 - 120 µL - possibility to extend up to 240 µL
<b>Sample Containers:</b>	0.5 mL, 2.0 mL, 4.0 mL cups and sample tubes (diameter 12 - 16 mm, length 75 - 100 mm)
<b>Sample Barcodes<sup>†</sup>:</b>	Code 128 and barcodes USS Codabar, Interleaved 2 of 5 and Code 39 with a check digit
<b>Sample Dispensing:</b>	CV ≤2% for volumes ≥2 µL

<sup>†</sup> used with sample tubes in a 9-pos. sample rack

### Reagents

Continuous access to reagents without interrupting test processing. Automatic identification via internal barcode reader. Clearly displayed real-time reagent volume and remaining test capacity. Up to four reagent additions per test.

<b>On-Board Capacity:</b>	42 positions in the cooled disk
<b>Reagent Volumes:</b>	2 - 240 µL
<b>Reagent Containers:</b>	10 mL and 20 mL vials
<b>Reagent Dispensing:</b>	CV ≤2% for volumes ≥2 µL

## Calibration

Factor, bias, linear, logit-log, spline, 2<sup>nd</sup> order and point-to-point calibration. Method-dependent use of individual calibrators or automatically diluted series from a stock calibrator. Previous curve comparison available.

## Quality Control

Real-time QC program with multiple, user-definable Westgard rules. Control frequency user-definable. Out-of-specification control results flagged. QC chart printouts, daily and cumulative reports.

## Dilutions

Automatic sample pre-dilution. Automatic dilution of over-range tests with automatic rerun. Addition of manual pre-dilution value for result calculation.

## Data Management

Windows® workstation with graphical user interface. Data input online, via mouse, touchscreen, keyboard and barcode reader. Different user groups can have different access rights. Different user interface language versions available.

<b>LIS Interface:</b>	CLSI LIS02-A2
<b>Hardware Interface:</b>	RS-232 or TCP/IP
<b>Result Reports:</b>	Collated by sample, manual entry of off-line results allowing for fully collated result reports, results calculated from both measured and off-line results. Spreadsheet reporting for further calculations possible.
<b>Traceability:</b>	Full traceability with long term storage of results including associated calibrations and reagent lot data.

Capacity:	Up to 350 tests/hour with one-reagent methods.
Dimensions and Weight:	94 cm (width) x 70 cm (depth) x 62/130 cm (height/with open cover), 110 kg (weight). Separate workstation.
Power Requirements:	100 - 240 VAC ±10%, 50-60 Hz ±5%, 300 W
Deionized Water Consumptions:	2.5 litres/ hour
Average Noise Level at 1 meter:	<60 dB(A)
Environmental Conditions:	Operating temperature range of 18 - 30 °C, humidity 40-80% (non-condensing)
Regulatory:	Conforms to CAN/CSA-C22.2 No.61010-1-04 UL Std. No. 61010-1:2004 FCC CFR 47 Part 15, subpart B 2011/65/EU RoHS Directive 2006/42/EC Machinery Directive 2004/108/EC EMC Directive <b>CE</b>
Ordering Codes:	9862 0001 Gallery Plus 9862 1001 Gallery Plus with the ECM unit

**Africa +43 1 333 50 34 0**  
**Australia +61 3 9757 4300**  
**Austria +43 810 282 206**  
**Belgium +32 92 72 54 82**  
**Brazil +55 11 3731 5140**  
**Canada +1 800 530 8447**  
**China 800 810 5118 (free call domestic)**  
**400 650 5118**  
**Denmark +45 70 23 62 60**  
**Europe-Other +43 1 333 50 34 0**  
**Finland +358 10 329 2200**  
**France +33 1 60 92 48 00**  
**Germany +49 6103 408 1014**  
**India +91 22 6742 9494**  
**Italy +39 02 950 591**

**Japan +81 6 6885 1213**  
**Korea +82 2 3420 8600**  
**Latin America +1 561 688 8700**  
**Middle East +43 1 333 50 34 0**  
**Netherlands +31 76 579 55 55**  
**New Zealand +64 9 980 6700**  
**Norway +46 8 556 468 00**  
**Russia/CIS +43 1 333 50 34 0**  
**Singapore +65 6289 1190**  
**Sweden +46 8 556 468 00**  
**Switzerland +41 61 716 77 00**  
**Taiwan +886 2 8751 6655**  
**UK/Ireland +44 1442 233555**  
**USA +1 800 532 4752**

Find out more at [thermofisher.com/discreteanalysis](http://thermofisher.com/discreteanalysis)

**ThermoFisher**  
SCIENTIFIC