SPECIFICATION SHEET

Harvey DI+ Cartridge System

Quick pure water for general lab use, humidification, and steam autoclaves

Thermo Scientific[™] Harvey[™] DI+ Cartridge System

- Turn-key system ships complete with a remote dispenser, Barnstead Pura-Lite indicator (50 KΩ.cm) and a high capacity, two-bed ion exchange cartridge to remove calcium, magnesium, and other ions from water
- The system accepts a broad range of other cartridges to remove impurities and produces pure water at a flow rate of up to 4 L/min
- Pressure regulator included
- Compact mounts to the wall for easy installation
- No need to store containers of distilled water

Operation

- Pura-lite notifies user when it is time to install a new cartridge
- Simple maintenance quarter-turn release canister
- Harvey DI+ Cartridge System provides pre-treated water at the push of a button



Specifications

	Overall dimensions W x H x D	Inlet connection	Feed water temperature	Max feed water pressure	Max flow rate	Voltage	Operating Weight
Harvey DI+	7 x 26 x 7 in (17.8 x 63 x 17.8 cm)	1/4" NPTF	4-49 °C (40-120 °F)	100 psig	4 L/min	120 Volts	13 lbs

Ordering Information

Description	Cat. No.			
Harvey DI + System (includes cartridge holder, wall bracket, Puralite indicator, dispenser, and DI cartridge)	AY1273X4			
High capacity replacement cartridge	D0803			
Optional feed water connection accessories				
Tubing (6 ft x 1/4" tubing); Qty. 1	TU494x4			
Feed water connection kit (multiple piece adapter to connect 3/4" NPTF X 1/4" NPTM to 1/4" tubing); Qty. 2	25.0071			

Find out more at thermofisher.com/purewater



Thermo Fisher