

Thermo Scientific DataRAM4 Particulate Monitor

Portable continuous particle sizing
monitor/dual wavelength nephelometer

The Thermo Scientific™ DataRAM 4 Particulate Monitor continuously monitors and logs the real-time concentration and median particle sizes of airborne dust, smoke, mist and fumes.

- Expanded I/O functionality and connectivity capabilities
- Easier component accessibility
- User interface designed for quick, easy operation and programming
- Accessible and interchangeable components
- Common electronics and spare parts



The Thermo Scientific DataRAM4 displays and records air temperature and humidity. In addition, air temperature and humidity are displayed and recorded.

With appropriate particle discriminators, it provides measurements correlated with PM10, PM2.5, PM1.0, and respirable fractions. The proprietary two-wavelength particle detection system provides the volume median particle diameter of the sampled aerosol, over a concentration range up to 400 mg/m³.

Unlike typical particle counting devices, the DataRAM 4 monitor is immune to particle coincidence errors, even at the highest concentrations. Volume median particle sizes down to 0.05 µm can be measured by this unique spectral nephelometric technique.

The DataRAM 4 monitors the concentrations of fine particulates in ambient air by a combination of aerodynamic size preselection, two wavelength nephelometry, and concurrent sensing/correction for relative humidity. This patented technique provides a continuous measurement of

PM2.5, independent of particle size and moisture- without heating, diffusion drying, or denuding the sample stream.

Additional features include:

- An isokinetic sampling probe/nozzle kit enables duct/stack monitoring.
- Self calibration extends unattended operation
- RS232 and RS485 data ports for bi-directional digital communications



Thermo
SCIENTIFIC

Thermo Scientific DataRAM4 Particulate Monitor

Concentration Measurement Range	0.0001 to 400 mg/m ³ (Auto ranging) Referenced to gravimetric calibration (NIST traceable) with SAE, Fine test dust (mmd - 2 to 3 µm, g = 2.5, as aerosolized)
Precision /Repeatability (2-sigma)	±1% of reading or ± 0.001 mg/m ³ , whichever is greater (1 second averaging) ±0.3% of reading or ±0.0001 mg/m ³ , whichever is greater (10 second averaging) For single-wavelength concentration sensing at 25°C
Accuracy	±2% of reading ± precision, referenced to gravimetric calibration (NIST traceable) with SAE fine test dust (mmd = 2 to 3 µm, g = 2.5, as aerosolized)
Resolution	0.1% of reading or 0.1 µg/m ³ , whichever is greater
Scattering Coefficient Range	10 ⁻⁷ to 0.4 m ⁻¹ (resolution: 3 significant digits, maximum)
Minimum Detection Limit	1.0 µg/m ³ (0.001 mg/ m ³) (1 second averaging) 0.3 µg/m ³ (0.003 mg/ m ³) (10 second averaging) 0.10 µg/m ³ (0.0001 mg/ m ³) (60 second averaging)
Visual Range (@λ = 550 nm)	0.001 to 337 km (resolution: 3 significant digits, maximum)
Angström Coefficient Measurement Range	0.0 to 4.0
Particle Sizing Range	(log-normal, g = 2.0, m = 1.50) 0.05 to 4 µm
Concentration Measurements	0.08 to 10 µm
Temperature Measurement Range	5° to 140° F (-15° to 60° C); accuracy: 0.05° C
Sampling Flow Rate Range	1.0 to 3.0 liters/min. (accuracy: 0.05 liters/min., adjustability: 0.1 liters/min.)
Measurement/Display Integration Time Range	1 to 60 sec. (selectable in 1-sec. steps)
Measurement/Display Update Frequency	1 per sec.
HEPA Filter Cartridge Replacement Frequency (typical)	less than 1 per 5 yrs (@ < 1 mg/m ³)
Alarm Level Range	Selectable over entire measurement range 0.001-400mg/m ³
Data Logging Averaging Periods	1 sec. to 24 hrs. (selectable in 1-sec. increments)
Data Logging Memory Capacity	50,000 data points in up to 99 tags (data sets)
Programmable Zeroing Periods	1 to 168 hrs. (selectable in 1-hr increments; if enabled, logging period must be >10 min.)
Elapsed Time Readout Range	1 sec. to 100,000 hrs. (over 11 yrs.), in sec., min., and hrs.
Digital Communications	RS232/RS485; full duplex, 9600 baud, software-controlled, filtered
Computer Requirements	IBM-compatible PC, Windows™ 95 or higher; 8 MB memory or more
Analog Outputs	0 to 5 V and 4 to 20 mA selectable full scale ranges between 0.1 and 400 mg/m ³
Power	Internal battery; rechargeable, sealed lead-acid, 6.5 Ahr, 6 V, 20-hr run time between charges (typical). AC line: universal voltage charger/power supply 100-250 V, 50-60 Hz (CE marked). Optional solar power system (Model DR-SOL).
Alarm Outputs	Alarm switch: 30 V (off,open), 2.5 A (on, closed) Alarm signal: 0 V (off), 5 V (on) (1 mA maximum load current) Audio alarm (back panel): more than 65 dB @ 1 m
Operating Environment	14° to 122° F (-10° to 50° C); 10 to 95% RH, non condensing
Storage Environment	-4° to 158° F (-20° to 70° C)
Dimensions	5.28 in. (134 mm) H x 7.25 in. (184mm) W x 13.63 in. (346 mm) D
Weight	11.7 lbs (5.3kg)
Standard Accessories Included	Universal voltage battery charger/power supply, standard HEPA filter cartridge, analytical filter holder, PC communications software disk, digital output cable, carrying case and instruction manual
Safety Approvals and Certificates	CE certification

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific products.

For more information, visit our website at thermoscientific.com/oeh

© 2012 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

USA
27 Forge Parkway
Franklin, MA 02038
Ph: (866) 282-0430
Fax: (508) 520-1460
customerservice.aqi@thermofisher.com

India
C/327, TTC Industrial Area
MIDC Pawane
New Mumbai 400 705, India
Ph: +91 22 4157 8800
india@thermofisher.com

China
+Units 702-715, 7th Floor
Tower West, Yonghe
Beijing, China 100007
+86 10 84193588
info.eid.china@thermofisher.com

Europe
Takkebijsters 1
Breda Netherlands 4801EB
+31 765795641
info.aq.breda@thermofisher.com